

product code: **AIR-GM04-20**



|                                  |                    |
|----------------------------------|--------------------|
| Nozzle quantity/type             | 4 x AIR-M200-...   |
| Blowing force at 5 bar [N]       | 23,2 - 32 - 43     |
| Air consumption at 5 bar [m3 /h] | 116 - 216 - 230    |
| Noise level at 5 bar [dB(A)]     | 85                 |
| Material                         | Anodised aluminium |
| Support material                 | Stainless steel    |
| Dimensions [mm]                  | 204x82x25          |
| Connection type                  | Female             |
| Rear connection                  | 3/8" x 1           |
| Side connection                  | 3/8" x 2           |
| Air flow type                    | Flat               |
| Pressure max [bar]               | 10                 |

## Warianty produktu

| Index  | Price  |
|--|--|
| <b>Four outlet 46004HF Manifold with four premounted AIR-M200-20<br/>AIR-GM04-20</b> | Product prices will become visible after signing in. |

## Product description

### Nóż powietrzny AIR-GM04 z czterema dyszami AIR-M200-20

Noże powietrzne EXTRA to rozwiązanie wykorzystujące kilka wysokojakościowych oraz spełniających normy OSHA i SUVA dysz powietrznych zamontowanych na kolektorze do odmuchu dużych powierzchni w warunkach przemysłowych.

Seria AIR-GM wykorzystuje do tego dysze płaskie serii AIR-M200 (od AIR-M200-4 do AIR-M200-28 - dostępne w wersji zarówno wykonanej z aluminium, jak i ze stali nierdzewnej), które posiadają wymienną wkładkę regulującą. Dysze serii AIR-M200 można łatwo otwierać. Umożliwia to czyszczenie jej wnętrza oraz konserwację, które pozwala na uniknięcie zatykania dyszy.

Noże powietrzne EXTRA zapewniają wzmocniony odmuch oraz wyraźną redukcję poziomu hałasu w porównaniu do stosowanych w przemyśle rur perforowanych. Niestandardowe rozmiary noży powietrznych są dostępne na życzenie klienta.