



product code: **SL04S**

| | |
|----------------------------------|----------------------|
| Nozzle quantity/type | 4 x AIR-147S-316L |
| Blowing force at 5 bar [N] | 14 |
| Air consumption at 5 bar [m3 /h] | 78 |
| Noise level at 5 bar [dB(A)] | 86.5 |
| Material | Stainless steel 316L |
| Support material | Stainless steel |
| Dimensions [mm] | 140x40x25 |
| Connection type | Female |
| Rear connection | 3/8" x 1 |
| Side connection | 3/8" x 2 |
| Air flow type | Flat |
| Pressure max [bar] | 10 |

Warianty produktu

| Index | Price |
|---|--|
| Four outlet 46004S Manifold with four premounted AIR-147S-316L SL04S | Product prices will become visible after signing in. |

Product description

Nóż powietrzny SL04S z czterema dyszami kątowymi ze stali nierdzewnej AIR-M147A-316L

Noże powietrzne EXTRA to rozwiązanie wykorzystujące kilka wysokojakościowych oraz spełniających normy OSHA i SUVA dysz powietrznych zamontowanych na kolektorze do odmuchu dużych powierzchni w warunkach przemysłowych.

Seria AIR-LR wykorzystuje do tego dysze kątowe serii AIR-M147A (w wersji wykonanej z aluminium lub ze stali nierdzewnej 316L).

Noże powietrzne EXTRA zapewniają wzmocniony odmuch oraz wyraźną redukcję poziomu hałasu w porównaniu do stosowanych w przemyśle rur perforowanych. Niestandardowe rozmiary noży powietrznych są dostępne na życzenie klienta.