

product code: **AIR-GM06S-8**



| | |
|----------------------------------|----------------------|
| Nozzle quantity/type | 6 x AIR-M200-...316L |
| Blowing force at 5 bar [N] | 34,8 - 48 - 64,5 |
| Air consumption at 5 bar [m3 /h] | 174 - 324 - 345 |
| Noise level at 5 bar [dB(A)] | 85 |
| Material | Stainless steel 316L |
| Support material | Stainless steel |
| Dimensions [mm] | 306x82x25 |
| Connection type | Female |
| Rear connection | 3/8" x 1 |
| Side connection | 3/8" x 2 |
| Air flow type | Flat |
| Pressure max [bar] | 10 |

Warianty produktu

| Index | Price |
|--|--|
| Six outlet 46006S Maniold with six premounted AIR-M200-316L-8 AIR-GM06S-8 | Product prices will become visible after signing in. |

Product description

Nóż powietrzny AIR-GM06 z sześcioma dyszami płaskimi ze stali nierdzewnej AIR-M200-316L-8

Noże powietrzne EXTRA to rozwiązanie wykorzystujące kilka wysokojakościowych oraz spełniających normy OSHA i SUVA dysz powietrznych zamontowanych na kolektorze do odmuchu dużych powierzchni w warunkach przemysłowych.

Seria AIR-GM wykorzystuje do tego dysze płaskie serii AIR-M200 (od AIR-M200-4 do AIR-M200-28 – dostępne w wersji zarówno wykonanej z aluminium, jak i ze stali nierdzewnej), które posiadają wymienną wkładkę regulującą. Dysze serii AIR-M200 można łatwo otwierać. Umożliwia to czyszczenie jej wnętrza oraz konserwację, które pozwala na uniknięcie zatykania dyszy.

Noże powietrzne EXTRA zapewniają wzmocniony odmuch oraz wyraźną redukcję poziomu hałasu w porównaniu do stosowanych w przemyśle rur perforowanych. Niestandardowe rozmiary noży powietrznych są dostępne na życzenie klienta.