

Karta produktu: Osuszacz adsorpcyjny HLA5600Pro -
wydajność 93,33 m3/min - ciśnienie 10 bar max -
moc 50 W



product code: **HLA5600Pro**

| | |
|---|--------------|
| Air flow [l/min] | 93333 |
| Flow rate [m3/h] | 5600 |
| Ciśnienie [bar] | 7 |
| Pressure max [bar] | 10 |
| Dewpoint [°C] | -40 |
| Standard complete drying cycle time [min] | 10 |
| Regeneration air consumption [m3/h] | 840 |
| Inlet temp. [°C] | 35-50 |
| Max. ambient temp. [°C] | 46 |
| Min. ambient temp. [°C] | 2 |
| Connection [BSP] | DN 150 PN 16 |
| Power supply [V/Ph/Hz] | 230/1/50-60 |
| Adsorbent | Alumina |
| Weight [kg] | 2950 |
| Hight [mm] | 2535 |
| Width [mm] | 2438 |
| Lenght [mm] | 1791 |

Warianty produktu

| Index | Price |
|--|--|
| Osuszacz adsorpcyjny HLA5600Pro - wydajność 93,33 m3/min - ciśnienie 10 bar max - moc 50 W HLA5600Pro | Product prices will become visible after signing in. |