Karta produktu: Oil-free vacuum claw pumps DVP PA 155



product code: PA 155

Nominal capacity [m3/h]	155
Total final pressure [mbar-hPa]	150
Maximum overpressure [bar-105Pa]	-
Motor power [KW] 1~/3~)	(-/3)
Nominal r.p.m [n/min]	2800
Noise level pump [Db (A)]	78
Noise level compressor [Db (A)]	-
Weight [Kg[N]] (1~/3~)	135 [1325]
Pump intake / outlet	1-1/2”G / 1”G
Oil quantity [dm3]	0,5
Operating temperature [°C]	-
Required room temp. for place of installation [°C]	0 ÷ 40
max humidity/ altitude	80% / 1000m s.l.m.

Warianty produktu

Index	Price
Oil-free vacuum claw pumps DVP PA 155 **PA 155**	Product prices will become visible after signing in.

Product description

Kłowa pompa próżniowa, bezolejowa PA 155, wydajność nom.: 155 m3/h; ciśnienie końcowe: 150 mbar; moc: 3 kW

Pompa kłowa PA 155 wytwarza próżnie w komorze sprężającej poprzez ruch obrotowy bezstykowych wirników kłowych. Niskie koszty serwisowe wynikają z braku tarcia elementów obracających się w komorze.

Pompa kłowa PA 155 wyposażona jest w:

- Regulowane złącze wlotowe.
- Tłumik na wylocie.
- Zawór regulujący podciśnienie (150 ÷ 500 mbar Abs.).
- Mocowania amortyzatorów.

Główne obszary zastosowań: obróbka drewna, termoformowanie, pakowanie, napowietrzanie wody, zastosowania chemiczno-farmaceutyczne, próżnia medyczna w klinikach dentystycznych i chirurgicznych, frezarki CNC, rekultywacja gleby, systemy transportu próżniowego.