



product code: VA 155-1

Nominal capacity [m3/h]	155
Total final pressure [mbar-hPa]	-
Maximum overpressure [bar-105Pa]	2
Motor power [KW] 1~/3~)	(-/7,5)
Nominal r.p.m [n/min]	2800
Noise level pump [Db (A)]	83
Noise level compressor [Db (A)]	-
Weight [Kg[N]] (1~/3~)	(-/147 [1442])
Pump intake / outlet	1-1/2"G / 1"G
Oil quantity [dm3]	0,5
Operating temperature [°C]	-
Required room temp. for place of installation [°C]	0 ÷ 40
max humidity/ altitude	80% / 1000m s.l.m

## Warianty produktu

Index	Price
Oil-free vacuum claw pumps DVP VA 155-1 VA 155-1	Product prices will become visible after signing in.

## Product description

**Kłowa pompa próżniowa, bezolejowa VA 155-1, wydajność nom.: 155 m3/h; maks. nadciśnienie: 2 bar; moc: 7,5 kW**

Pompa kłowa VA 155-1 wytwarza objętość powietrza i transportuje je przez kanał wlotowy do kanału wylotowego poprzez obrót dwóch wirników kłowych. Bezstykowy obrót wirników jest synchronizowany przez przekładnię bez oleju, co pozwala uniknąć tarcia podczas obrotu.

Pompa kłowa VA 155-1 wyposażona jest w:

- Regulowane złącze wlotowe.
- Zawór nadmiarowy ciśnienia na wylocie.
- Mocowania amortyzatorów.

Główne obszary zastosowań: napowietrzanie wody, rekultywacja gleby.