



product code: **CB 12**

Nominal capacity [m3/h]	12
Maximum overpressure [bar-105Pa]	0,6
Motor power [KW] 1~/3~)	0,37 / 0,45
Nominal r.p.m [n/min]	1400
Noise level pump [Db (A)]	64
Weight [Kg[N]] (1~/3~)	14,5 [142,2] / 13,5 [132,4]
Pump intake / outlet	1/2"G / 1/2"G
Operating temperature [°C]	70 ÷ 75
Required room temp. for place of installation [°C]	0 ÷ 40
max humidity/ altitude	80% / 1000m s.l.m

Warianty produktu

Index	Price
Oil-free rotary vane vacuum pumps CB 12 CB 12	Product prices will become visible after signing in.

Product description

Łopatkowa pompa próżniowa, bezolejowa CB 12, wydajność nom.: 12 m3/h; ciśnienie końcowe: 0,6 mbar; moc: 0,37 kW

Pompa próżniowa CB 12 ma ograniczone rozmiary i wagę, może być instalowane na ograniczonej przestrzeni, pod warunkiem dobrej wentylacji. Przemysłowa konstrukcja monoblokowa z wirnikiem zamontowanym bezpośrednio na wale silnika oraz zastosowanie lekkich stopów. Chłodzenie sprężarki zapewnia zintegrowany wentylator silnika.

Łopatkowa pompa próżniowa CB 12 jest wyposażona w: Filtr ochronny na wlocie.

Główne obszary zastosowań: przemysł budowlany.