

product code: **ZA 60S**

Nominal capacity [l/min]	60
Total final pressure [mbar-hPa]	30
Motor power [KW] 1~/3~)	(0,27/-)
Nominal r.p.m [n/min]	1400
Noise level pump [Db (A)]	52
Weight [Kg[N]] (1~/3~)	(8,7[85,3]/-)
Operating temperature [°C]	40 ÷ 45
Required room temp. for place of installation [°C]	12 ÷ 40
max humidity/ altitude	80% / 1000m s.l.m.

Warianty produktu

Index	Price
Oil-free vacuum piston pumps ZA 60S ZA 60S	Product prices will become visible after signing in.

Product description

Tłokowa pompa próżniowa, bezolejowa ZA 60S, wydajność nom.: 60 l/min.; ciśnienie końcowe: 30 mbar; moc: 0,27 kW

Pompa tłokowa ZA 60S łączy w sobie najlepsze cechy tradycyjnych pomp tłokowych i pomp membranowych w małej jednostce o doskonałych właściwościach. Pompa tłokowa ZA 60S idealnie nadają się do zastosowań, w których mgła olejowa jest niepożądana. Co więcej, bezolejowa konstrukcja sprawia, że okresy międzyobsługowe są bardzo długie.

Pompa ZA 60S wyposażona jest w:

- Zabezpieczenie termiczne (130°C).
- Przewód zasilający (z spinem CEE22).
- Mocowania amortyzatorów.
- Tłumik.

Obszary zastosowań poczty: elektromedycyna, przenośniki przyssawkowe, zastosowania laboratoryjne i budownictwo.