

product code: **ZB 15**

Nominal capacity [l/min]	14
Total final pressure [mbar-hPa]	220
Maximum overpressure [bar-105Pa]	-
Power supply [V]	230±10%
Motor power [W]	95
Current drawn [A]	0,6
Noise level pump [Db (A)]	58
Weight [Kg[N]] (1~/3~)	1,6[15,69]
Required room temp. for place of installation [°C]	0 ÷ 40
max humidity/ altitude	80% / 1000m s.l.m.

Warianty produktu

Index	Price
Oil-free vacuum piston pumps ZB 15 ZB 15	Product prices will become visible after signing in.

Product description

Tłokowa pompa próżniowa, bezolejowa ZB 15, wydajność nom.: 14 l/min.; ciśnienie końcowe: 220 mbar; moc: 0,095 kW

Pompa tłokowa ZB 15 została specjalnie zaprojektowana do zastosowań w stomatologii, urządzeniach medycznych, przemyśle lekkim. Konstrukcja projektowa wymaga montażu pompy w bezpiecznym środowisku. Nie są wymagane żadne przestoje, ponieważ jednostka pracuje w trybie ciągłym (S1).

Pompa ZB 15 wyposażona jest w:

- Mocowania amortyzatorów.
- Tłumik.
- Zabezpieczenie termiczne (120°C).

Główne obszary zastosowań: stomatologia, urządzenia medyczne, hobby i zastosowania w przemyśle lekkim.