Karta produktu: Hose reel without hose. Capacity: 50 m 3/8" 2SC-400 bar hose - In. 3/8" F - Out. 3/8" M



**product code:** **BGLD4H3850ST**

| | |
|---|---|
| **Medium** | **Woda 150°** |
| **Ciśnienie [bar]** | **400** |
| **Średnica wlotu** | **3/8"F** |
| **Średnica wylotu** | **3/8"M** |
| **Waga [kg]** | **49** |

## Warianty produktu

| Index | Price |
|---|---|
| **Hose reel without hose. Capacity: 50 m 3/8" 2SC-400 bar hose - In. 3/8" F - Out. 3/8" M**<br>**BGLD4H3850ST** | **4 955,20 zł**<br>**+VAT 23%**<br>Ask your account manager for a better price |

## Product description

### Automatyczne zwijadło do węża seria "BGL/BGLD" - BGLD4H3850ST (model bez węża w zestawie)

Zwijadła węży serii BGL/BGLD przeznaczone są do rozprowadzania mediów takich, jak olej napędowy, olej, powietrze, woda o różnych parametrach temperatury i ciśnienia.

#### Konstrukcja zwijadła:

- Wykonane jest z galwanizowanej na gorąco odlewanej stali,
- Pokryte elektrostatycznym proszkiem poliestrowym odpornym na działanie promieni UV,
- Elementy pozostające w kontakcie z medium obróbce podwyższającej ich odporność na korozję,

Otwarta budowa umożliwia łatwy montaż i wymianę węża oraz pozwala na kontrolę zwijania węża.

Modele z wężem dostarczane są z elastycznym przewodem podłączeniowym do instalacji.

Zwijadło wyposażone jest w pojedynczą, która automatycznie zwija wąż oraz blokadę umożliwiającą blokowanie węża po wyciagnięciu na żądaną długość. Prowadnica węża może być zablokowana w trzech pozycjach zależnie od położenia zwijadła.

#### OPCJA: obrotowa płyta montażowa.