Karta produktu: Hose reel with rubber hose 8x14 (5/16") length 15 m - In. 3/8" F - Out. 3/8" M



**product code: V180815**

| | |
|---|---|
| **Measured medium** | **Air/Water** |
| **Ciśnienie [bar]** | **18** |
| **Średnica wlotu** | **3/8"F** |
| **Średnica wylotu** | **3/8"M** |
| **Hose diam.** | **8 x 14** |
| **Długość węża [m]** | **15** |
| **Hose material** | **Rubber** |
| **Weight [kg]** | **17** |

## Warianty produktu

| Index | Price |
|---|---|
| **Hose reel with rubber hose 8x14 (5/16") length 15 m - In. 3/8" F - Out. 3/8" M**<br>**V180815** | Product prices will become visible after signing in. |

## Product description

### Automatyczne zwijadło do węża seria "V" - V180815 (wąż gumowy w zestawie)

Automatyczne zwijadła węży serii V przeznaczone są do rozprowadzania mediów o kilku wartościach temperatury i ciśnienia.

#### Konstrukcja zwijadła:

- Wykonane jest z galwanizowanej na gorąco i odlewanej stali,
- Pokryte elektrostatycznym proszkiem poliestrowym odpornym na działanie promieni UV,
- Elementy pozostające w kontakcie z medium obróbce podwyższającej odporność na korozję,
- Otwarta budowa umożliwia łatwy montaż i wymianę węża oraz pozwala na kontrolę zwijania węża.

Zwijadło wyposażone jest w sprężynę, która automatycznie zwija wąż oraz blokadę umożliwiającą blokowanie węża po wyciągnięciu na żądaną długość Prowadnica węża może być zablokowana w trzech pozycjach zależnie od położenia zwijadła.

**OPCJE: modele wyposażone w węże specjalne; boczne panele ochronne; elastyczny przewód podłączeniowy do instalacji; prowadnica węża z 4 rolkami; obrotowa podstawa; dodatkowe mocowanie skracające czas montażu zwijadła.**