Karta produktu: Hose reel with hose 3/4" EN 857 1SC L= 20 m - Connection-hose In. 3/4" F-Out. 3/4" F



**product code:** **BG603420**

| | |
|---|---|
| **Measured medium** | **Oil** |
| **Ciśnienie [bar]** | **60** |
| **Średnica wlotu** | **3/4"F** |
| **Średnica wylotu** | **3/4"F** |
| **Hose diam.** | **3/4"** |
| **Długość węża [m]** | **20** |
| **Hose material** | **1SC Rubber** |
| **Weight [kg]** | **44** |

## Warianty produktu

| Index | Price |
|---|---|
| **Hose reel with hose 3/4" EN 857 1SC L= 20 m - Connection-hose In. 3/4" F-Out. 3/4" F**<br>**BG603420** | **5 083,57 zł**<br>**+VAT 23%**<br>Ask your account manager for a better price |

## Product description

### Automatyczne zwijadło serii "BG" - BG603420 (wąż "LEANLINE" w zestawie)

Automatyczne zwijadła węży serii BG przeznaczone są do rozprowadzania mediów o różnych wartościach temperatury i ciśnienia.

#### Konstrukcja zwijadła:

- Wykonane jest z galwanizowanej na gorąco i odlewanej stali,
- Pokryte elektrostatycznym proszkiem poliestrowym odpornym na działanie promieni UV,
- Elementy pozostające w kontakcie z medium są poddawane obróbce podwyższającej odporność na korozję,
- Bęben obraca się na łożyskach zmniejszających tarcie i podwyższających funkcjonalność.

Zwijadło wyposażone jest w sprężynę, która automatycznie zwija wąż oraz blokadę umożliwiającą blokowanie węża po wyciagnięciu na żądaną długość. Prowadnica węża może być zablokowana w trzech pozycjach zależnie od położenia zwijadła.

Modele z wężem dostarczane są z elastycznym przewodem podłączeniowym do instalacji

#### Opcja: obrotowa podstawa